

SAFETY DATA SHEET BBJ POWER Coil Clean®

BBJ Environmental Solutions "The standard of care for indoor air"

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product Name: BBJ POWER Coil Clean®

Product Codes(s): 520-04; 525-01; 523-01; 575-01 Synonym(s): Aqueous ammonium bifluoride solution REACH Registration Number: No data available

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Cleaner for HVAC and refrigeration evaporator and condenser coil cleaner

Uses advised against: No uses advised against

1.3 Details of the supplier and of the safety data sheet

Manufacturer/Distributor BBJ Environmental Solutions 6321 Pelican Creek Circle Riverview, FL 33578 USA

+1-813-622-8550; Toll free: +1-800-889-2251

1.4 Emergency telephone number: Chemtrec (24 hours) +1-800-424-9300

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Product definition: Mixture

Classification in accordance with 29 CFR 1910 (OSHA HCS) and Regulation (EC) No 1272/2008

Acute Toxicity, Inhalation - Category 5 [H333] Acute Toxicity, Dermal - Category 3 [H311] Acute Toxicity, Oral - Category 3 [H301] Skin Corrosive - Category 1B [H314]

2.2 Label Elements

Hazard Symbol(s):



GHS05

Signal Word: Danger

Hazard Statement(s): H333 - May be harmful if inhaled H311 - Toxic in contact with skin

H301 - Toxic if swallowed

H314 - Causes severe skin burns and eye damage

Precautionary Statements:

[Prevention] P260 - Do not breathe mist, vapor or spray.

P264 - Wash hands and other skin areas exposed to material thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves, protective clothing, eye protection and face protection.

[Response] P301 + P330 + P331 + P310 - IF SWALLOWED: Rinse mouth. Do not induce vomiting.Immediately call a

POISON CENTER or doctor.

P303 + P361 + P353 - IF ON SKIN: Remove immediately all contaminated clothing. Rinse skin with water or

shower.

P263 - Wash contaminated clothing before reuse.

P304 + 312: IF INHALED: Call a POISON CENTER or doctor.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P321 + P322 - Specific treatment: Contact POISON CENTER or doctor immediately. Refer to Section 4

of this SDS.

[Storage] P405 - Store locked up.

[Disposal] P501 - Dispose of contents and container in accordance with national and local regulations.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

BBJ POWER Coil Clean Page 1 of 7

3.2 Mixtures

% by Weight	Ingredient	CAS Number	EC Number	Index Number	GHS Classification
<5	Ammonium bifluoride	1341-49-7	215-676-4	009-009-00-4	H301, H314
<1	Cocamide diethanolamine	68603-42-9	271-657-0		H315, H318
≤2	Hydrofluoric acid	7664-39-3	231-634-8	009-003-00-1	H300, H310, H314, H330
<0.2	Diethanolamine	111-42-2	203-868-0	603-071-00-1	H302, H315, H318, H373

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4 - FIRST AID MEASURES

This product contains approximately 2% free hydrofluoric acid (HF). Solutions of 2% or less hydrofluoric acid can cause burns. First aid techniques for treatment of hydrofluoric acid exposures are unique. Even low levels of exposure to HF require a rapid response and the use of calcium (most commonly calcium gluconate solutions or gels) to scavenge and neutralize the fluoride ion. Effects may be delayed, so treatment should be given even if exposure is suspected.

4.1 Description of first aid measures

Inhalation: Move the exposed person to fresh air immediately. If breathing is difficult or irregular, administer oxygen; if respiratory arrest occurs, start artificial respiration by trained personnel. Do not use mouth-to-mouth method if the victim inhaled this product; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If unconscious, maintain an open airway. Loosen tight fitting clothing such as a collar, tie, belt or waistband. Get Immediate medical attention. Calcium gluconate 2.5% in normal saline may be given by nebulizer with oxygen. If unavailable, four calcium gluconate (500 mg) tablets should be given by mouth every two hours until the victim is admitted to the hospital.

Eyes: Immediately flush eyes with large amounts of water for at least 20 minutes, keeping eyelids apart and away from the eyeball. Remove contact lenses, if present and easy to do, after the first 2 minutes and continue rinsing. Immediately contact a doctor, preferably an ophthalmologist. If a doctor is not immediately available, apply one or two drops of 0.5% tetracaine hydrochloride solution or other topical ophthalmic anesthetic and continue irrigation. Do not use skin treatment preparations for burns for the eyes. Use no oils or greases unless instructed to do so by a doctor. Irrigate with 1% calcium gluconate in normal saline for one to two hours to prevent or lessen corneal damage.

Skin: Flush skin with large amounts of water while removing contaminated clothing using PVC gloves and continue rinsing for at least 15 minutes. Apply and continually massage calcium gluconate gel (2.5%) into the burn area with gloved fingers until the pain is relieved. Use of local pain killers (anesthetics) is not recommended as reduction in pain is an indicator of the effectiveness of the treatment. Seek immediate medical attention. For large or severe burns four calcium gluconate (500 mg) tablets should be given by mouth every two hours, until the victim receives medical care.

Ingestion: Get immediate medical assistance. Rinse mouth with water if the victim is conscious. Remove dentures if any. DO NOT induce vomiting. Give 3 - 4 glasses of water to drink if the victim is conscious and alert and able to swallow. Give four calcium gluconate (500 mg) tablets every two hours; if not available, give the victim milk or milk of magnesia. Never give anything by mouth to an unconscious or convulsing person. Do not leave the victim unattended. To prevent aspiration of swallowed material lay the victim on one side with the head lower than the waist.

4.2 Most important symptoms and effects, both acute and delayed

Potential health symptoms and effects

Eyes: Causes serious burns to the eyes. Symptoms include pain, redness, swelling and tearing. May cause permanent eye damage, including blindness.

Skin: Causes skin irritation and burns to the skin. Skin exposures can cause symptoms ranging from minor skin irritation to painful redness and swelling. Effects of skin contact may not be immediate and contact may not be painful at first. Severe burns can occur if treatment is delayed after exposure. Burns may appear stable only to get much worse several hours after exposure. Dilute solutions may have a reduced effect. May be toxic if absorbed through the skin. May cause hypocalcemia and other toxic effects.

Inhalation: Harmful if inhaled. Causes irritation to the nose, throat and respiratory tract. Symptoms may include headache, chest pains and cough. Aspiration of product during vomiting may cause pulmonary edema and pneumonitis (fluid on the lungs and inflammation of the lungs). Breathing difficulties that may be delayed in onset.

Ingestion: Causes burns to the mouth, mucous membranes, throat, esophagus and stomach. May cause perforation of the stomach and esophagus. May be toxic if swallowed. Symptoms may include nausea, vomiting, abdominal pain and diarrhea, difficulty breathing, swelling of the throat, unconsciousness, coma and possible heart failure. Ingestion may also result in the fluoride ion binding with calcium to produce abnormally low levels of serum calcium (hypocalcaemia), which will impair many necessary physiological functions in the body (e.g. muscle contractions). Systemic toxicity is likely to occur unless medical treatment is immediate.

Chronic: Prolonged or repeated skin contact may lead to necrosis of the skin. Chronic fluoride poisoning can cause severe bone changes, loss of weight, anemia and dental defects. Repeated or prolonged exposures may cause sore throat, nosebleeds and chronic bronchitis. Chronic inhalation may cause hypocalcemia with nervous problems (tetany) and cardiac arrhythmia (reduced calcium levels, spasms and irregular heart beat).

4.3 Indication of any immediate medical attention and special treatment needed

Advice to Doctor and Hospital Personnel

First aid and medical treatment must be specific for Hydrofluoric Acid Solutions. The damage caused by this product is far more extensive than that caused by solutions of hydrochloric or other acids. Hydrofluoric Acid penetrates deeply and rapidly below fat layers, binding and depleting tissue calcium. Failure to start or provide correct medical treatment may be fatal.

SECTION 5 - FIRE FIGHTING MEASURES

5.1 Extinguishable media

Suitable methods of extinction: Use media extinguishing media suitable for surrounding material.

Unsuitable methods of extinction: None known

BBJ POWER Coil Clean Page 2 of 7

5.2 Special hazards arising from the substance or mixture

Unusual fire and explosion hazards: Solution may release hydrogen fluoride when heated. Releases ammonia when solution is mixed with alkalis. Potential sources of ignition should be removed from the area. Closed containers may explode due to the buildup of pressure when exposed to extreme heat.

Hazardous decomposition products: May react with some metals to form potential flammable and toxic gases. During a fire the water contained in this product may evaporate, leaving a residue that may combust, producing corrosive fumes of fluorides as well as carbon monoxide and other unidentifiable organic compounds. Symptoms may not be immediately apparent or may be delayed. Obtain medical attention immediately.

Explosion hazards: Release of hydrogen gas during a fire can form explosive mixtures with air, especially in confined spaces.

5.3 Advice for firefighters

Wear full protective equipment including self-contained breathing apparatus, a full acid resistant suit, PVC gloves and enclosed footwear. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. Water contaminated by this material must be contained from being discharged to any waterway, sewer or drain to prevent environmental contamination.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear appropriate protective clothing designated in Section 8. Evacuate non-essential personnel. Remove all sources of ignition. Good ventilation is necessary. Discharged material may produce hydrogen fluoride fumes. Spills should be cleaned up promptly to avoid damage to surrounding materials.

6.2 Environmental precautions

Avoid dispersal of spilled material or runoff and prevent contact with soil and entry into drains, sewers or waterways.

6.3 Methods and materials for containment and cleaning up

Approach the release from upwind. Cover drains and contain spill. Avoid drainage to areas that cannot be treated. Cover with a large quantity of non-combustible, inert absorbent (e.g. sand, vermiculite, diatomaceous earth). DO NOT use combustible absorbent such as sawdust. DO NOT use combustible absorbent such as sawdust. Collect using non-sparking tools and place into an approved container for proper disposal. Observe possible material restrictions (Sections 7.2, 10.5 and 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material poses the same hazard as the spilt product.

Spills and releases may have to be reported to Federal and/or local authorized. See Section 15 regarding reporting requirements.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for safe handling

Wear all appropriate personal protective equipment specified in Section 8. Do not get in eyes or on skin or clothing. Do not breathe mist or vapor. Do not ingest. If normal use of material presents a respiratory hazard, use only adequate ventilation or wear an appropriate respirator.

Advice on protection against fire and explosion

Keep away from heat and incompatible materials.

7.2 Conditions for safe storage, including any incompatibilities

Store in original container in a dry, cool and well ventilated area, away from incompatible materials (see Section 10.5) and food and drink. Solution becomes cloudy at temperatures <4.4 °C (<40 °F). Transfer only to approved containers having correct labeling. Do not transfer to or store in glass containers. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers retain product residue and are hazardous. DO NOT reuse containers. Use appropriate containment to avoid environmental contamination. Ventilate enclosed areas. Do not take internally. Keep locked up and out of reach of children.

7.3 Specific end uses

Apart from the uses mentioned in Section 1.2, no other specific uses are stipulated.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Occupational exposure limits

CAS Number	Ingredient	OSHA	ACGIH	NIOSH
7664-39-3	Hydrofluoric Acid	3 ppm TWA	0.5 ppm TWA; 2 ppm Ceiling	3 ppm; 2.5 mg/m³ TWA; 6 ppm; 5 mg/m³ Ceiling; 30 ppm IDLH
111-42-2	Diethanolamine		1 mg/m³ TWA	3 ppm; 15 mg/m ³ TWA

8.2 Exposure controls

Engineering measures: Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. Use adequate ventilation. Local exhaust is preferable.

Individual protection measures: Wear protective clothing to prevent repeated or prolonged contact with product. Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the representative supplier.

Hygiene measures: Facilities storing or using this material should be equipped with an eyewash station and safety shower. Change contaminated clothing. Preventive skin protection is recommended. Wash hands thoroughly after use, before eating, drinking or using the lavatory.

Eye/face protection: Wear protective goggles or safety glasses with unperforated side shields during use. A full face shield is recommended if splashing occurs during use. Refer to 29 CFR 1910.133, ANSI Z87.1or European Standard EN 166.

BBJ POWER Coil Clean Page 3 of 7

Hand protection: Wear gloves recommended by glove supplier for protection against materials in section 3. Gloves should be impermeable to chemicals and oil. Breakthrough time of selected gloves must be greater than the intended use period.

Other protective equipment: Protective clothing. Wear protective boots if the situation requires.

Respiratory protection: Always use an approved respirator when vapor/aerosols are generated. Where risk assessment shows air-purifying respirators are appropriate use a full-faced respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Environmental exposure controls: Do not empty into drains.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Clear, colorless to pale yellow liquid

Odor Mild

Odor Threshold No data available Molecular Weight Not applicable **Chemical Formula** Not applicable 5.4 - 5.6 0 °C (32 °F) Freezing/Melting Point, Range 100 °C (212 °F) **Initial Boiling Point** Evaporation Rate No data available Flammability (solid, gas) Not applicable Flash Point No data available

Autoignition Temperature

Decomposition Temperature
Lower Explosive Limit (LEL)
Upper Explosive Limit (UEL)
Vapor Pressure
Vapor Density
Specific Gravity

No data available
No data available
17 mm Hg
>1 (Air = 1)
1.00 - 1.05

Viscosity No data available
Solubility in Water Miscible

Partition Coefficient: n-octanol/water No data available

Volatiles by Volume @ 21 °C >85%

9.2 Other data

No data available

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

No special reactivity has been reported.

10.2 Chemical stability

Stable under recommended storage conditions, handling and use.

10.3 Possibility of hazardous reactions

May generate hydrogen fluoride when heated. Releases ammonia when in contact with alkalis.

10.4 Conditions to avoid

Extreme temperatures. Contact with incompatible materials. DO NOT mix with other cleaning agents or household chemicals, including ammonia, acids, alkalis, bleaches or chlorine containing cleaners. DO NOT transfer product to or store product in glass containers.

10.5 Incompatible materials

Strong oxidizing agents, strong alkalis, strong bases, strong reducing agents, metals and metal powders, sulfides, cyanides

10.6 Hazardous decomposition products

Thermal decomposition products include hydrogen fluoride gas, hydrogen gas, oxides of carbon, ammonia and nitrogen oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute Oral Toxicity

Hydrofluoric Acid solutions can be fatal if swallowed.

Acute inhalation toxicity

No data available

Acute dermal toxicity

No data available

Skin irritation

Causes skin burns

Eye irritation

Causes burns and possible eye damage

Sensitization

No data available

BBJ POWER Coil Clean Page 4 of 7

Genotoxicity in vitro

No data available

Mutagenicity

No data available

Specific organ toxicity - single exposure

No data available

Specific organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Further information

Diethanolamine (CAS #111-42-2): IARC Group 2B Carcinogen - Possibly carcinogenic to humans. Not identified as a probable, possible, potential or confirmed carcinogen by ACGIH, NTP or OSHA.

Cocoamide DEA (CAS #68603-42-9): IARC Group 2B Carcinogen - *Possibly carcinogenic to humans*. Not identified as a probable, possible, potential or confirmed carcinogen by ACGIH, NTP or OSHA.

No data is available regarding the mutagenicity or teratogenicity of this product, nor is there any available data that indicated that it causes adverse developmental or fertility effects.

Handle in accordance with good industrial hygiene and safety practice. Product should be handled with care.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Toxicity

The aquatic toxicity of this product has not been evaluated.

Acute and prolonged toxicity to fish - Hydrofluoric Acid: Fish (fresh water), lethal concentration: 60 ppm (time period not specified)

12.2 Persistence and degradability

The organic components of this product are biodegradable. Inorganic substances are not biodegradable. Methods for the determination of biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulation potential

Not expected to bioaccumulate

12.4 Mobility in soil, water

Expected to have high mobility in soil.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available.

12.6 Other adverse effects

Additional ecological information

Do not allow material to run into surface waters, wastewater or soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Methods of disposal: The generation of waste should be avoided or minimized whenever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Hazardous waste: The classification of this product may meet the criteria for a hazardous waste.

SECTION 14 - TRANSPORT INFORMATION

Note: Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

US DOT (Domestic Ground Transportation)

Proper Shipping Name: Corrosive liquid, n.o.s. (Hydrofluoric Acid, Ammonium Bifluoride)

Hazard Class: 8
UN/NA: UN1760
Packing Group: III

Packaging Authorization: Non-Bulk: 49 CFR 173.203; Bulk: 173.241

Guide #154

Packaging Exceptions: 49 CFR 173.154

IMO/IMDG (Water Transportation)

NAERG:

Proper Shipping Name: Corrosive liquid, n.o.s. (Hydrofluoric Acid, Ammonium Bifluoride)

Hazard Class: 8
UN/NA: UN1760
Packing Group: III
Marine Pollutant: No
EMS Number: F-A, S-B



BBJ POWER Coil Clean Page 5 of 7

ICAO/IATA (Air Transportation)

Proper Shipping Name: Corrosive liquid, n.o.s. (Hydrofluoric Acid, Ammonium Bifluoride)

Hazard Class: 8 UN/NA: UN1760

Packing Group:

Quantity Limitations: 49 CFR 173.27 and 175.75 - Cargo Aircraft Only: 60 l; Passenger Aircraft: 5 l

RID/ADR (Rail Transportation)

Proper Shipping Name: Corrosive liquid, n.o.s. (Hydrofluoric Acid, Ammonium Bifluoride)

Hazard Class: 8
UN/NA: UN1760
Packing Group: III

SECTION 15 - REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for substance or mixture

U. S. Federal Regulations

OSHA Hazard Communication Standard: This material is classified as hazardous in accordance with OSHA 29 CFR 1910-1200.

OSHA Process Safety Management Standard: Hydrofluoric Acid (CAS # 7664-39-3) is regulated under OSHA PSM Standard 29 CFR 1910.119.

EPA Risk Management Planning Standard: Hydrofluoric Acid (CAS #7664-39-3) is regulated under EPA RMP Standard (RMP) 40 CFR Part 68.

EPA Federal Insecticide, Fungicide and Rodenticide Act: This product is not a registered Pesticide under the FIFRA, 40 CFR Part 150.

TSCA Status: All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory. This product is subject to TSCA 12(b) Export Notification.

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories: Acute Health Hazard, Chronic Health Hazard

SARA 313 Information: Hydrofluoric Acid (CAS #7664-39-3) is subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to Know Act of 1986.

SARA 302/304 Extremely Hazardous Substance: Hydrofluoric Acid is subject to reporting requirements of these sections of Title III of SARA.

SARA 302/304 Emergency Planning & Notification: Hydrofluoric Acid Is subject to reporting requirements of these sections of Title III of SARA.

Comprehensive Response Compensation and Liability Act (CERCLA): This product contains the following CERCLA reportable substances: Ammonium Bifluoride (CAS #1341-49-7), RQ - 45.36 kg (100 lbs)

Hydrofluoric Acid (CAS #7664-39-3), RQ - 45.36 kg (100 lbs)

Clean Air Act (CAA)

Hydrofluoric Acid (CAS #7664-39-3), as 100% HF, is listed as a Hazardous Air Pollutant (HAP) as designated in CAA Section 112 (b).

Hydrofluoric Acid (CAS #7664-39-3), as 100% HF, is found on the CAA Section 112 (b) list of Accidental Release Prevention Substances.

This product does not contain any Class 1 or Class 2 Ozone depletors.

Clean Water Act (CWA)

Hydrofluoric Acid is listed as Hazardous Substances under the CWA.

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

U.S. State Regulations

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

Cocamide DEA (CAS #68603-42-9) and Diethanolamine (CAS # 111-42-2) are known to the State of California to cause cancer.

Other U.S. State Inventories

Hydrofluoric Acid (CAS #7664-39-3) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants List(s): CA, DE, ID, IL, ME, MA, MN, NC, NJ, NY, PA, RI, WA, WI.

Diethanolamine (CAS #111-42-2) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/Air Pollutants List(s): CA, MA, MN, NJ, PA.

Canada

WHMIS Hazard Symbol and Classification



D1B - Materials causing immediate and serious toxic effects



D2A - Materials causing other toxic effects



E - Corrosive

Canadian National Pollutant Release Inventory (NPRI): Hydrofluoric Acid and Diethanolamine are listed on the NPRI.

European Economic Community

Labeling (67/548/EEC or 1999/45/EC)



T+ - Very toxic



C - Corrosive

Risk Phrases: R27/28 - Toxic in contact with skin and if swallowed.

R35 - Causes severe burns.

Safety Phrases: S1/2 - Keep locked up and out of the reach of children.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection.

S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible).

WGK, Germany (Water danger/protection): 1

BBJ POWER Coil Clean Page 6 of 7

Global Chemical Inventory Lists

Country	Inventory Name	Inventory Listing*	
Canada:	Domestic Substance List (DSL).	Yes	
Canada:	Non-Domestic Substance List (NDSL).	No	
Europe:	Inventory of New and Existing Chemicals (EINECS)	Yes	
United States:	Toxic Substance Control Act (TSCA)	Yes	
Australia:	Australian Inventory of Chemical Substances (AICS)	Yes	
New Zealand:	New Zealand Inventory of Chemicals (NZIoC)	Yes	
China:	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
Japan:	Inventory of Existing and New Chemical Substances (ENCS)	Yes	
Korea:	Existing Chemicals List (ECL)	Yes	
Philippines:	Philippines Inventory of Chemicals and Chemical Substances (PICCS)	Yes	

^{*}Yes - All components of this product are in compliance with the inventory requirements administered by the governing country.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SECTION 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)

Health * 3 **Flammability** 0 **Physical Hazard** 1 Personal Protection C

HMIS and NFPA Hazard Rating Legend

* = Chronic Health Hazard 2 = MODERATE 0 = INSIGNIFICANT 3 = HIGH1 = SLIGHT 4 = EXTREME

National Fire Protection Association (NFPA)

Instability

Flammability



Special







Full text of GHS Hazard Phrases referenced in Section 3 (not covered in Section 2)

H300 - Fatal if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H315 - Causes skin irritation

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H373 - May cause damage to organs through prolonged or repeated exposure

BBJ Environmental Solutions assumes no legal responsibility or liability from the described product's use. All chemicals possess unknown potential hazards. The information herein should be used only to supplement the end user's existing knowledge. Read directions for proper use. This SDS was written for the product as packaged. Cleaning Contractors shall comply with all applicable OSHA regulations.

Revision 2: 5 April 2016 Revision 1: 18 October 2012

BBJ POWER Coil Clean Page 7 of 7

No - One or more components of this product are not on the inventory and are not exempt from listing.